



Category
SAFE

Connection
FLANGE
SCREWED MALE/SCREWED SOCKET






Form
ANGLE PATTERN

GLOBE													
THUMBNAIL	SERIES	PN 6	PN 10	PN 16	PN 25	PN 40	PN 63	PN100	PN160	ANSI150	ANSI300	ANSI900-2500	DN
	SAFE			●		●							15-250
	SAFE-P			●		●							15-150
	SAFE-P 920 - DISC					●							G1"XG1 1/2"-G3/4"- G1"
	SAFE-TC					●							G1/2"- G1"
	SAFE-TCP							●					G1/2"- G1"
	SAFE-TCS							●					G1/2"- G1"
	SAFE-SN ANSI									●	●		15-150 (ANSI 1"- 6")
	REYCO® R ANSI											●	ASA900, ASA1500 - 1 1/2" - 4", ASA2500 - 1 1/2"-2"
	REYCO® RL ANSI											●	15 -200 (ANSI 1"- 2")

THUMBNAIL	SERIES	PN 6	PN 10	PN 16	PN 25	PN 40	PN 63	PN100	PN160	ANSI150	ANSI300	ANSI900-2500	DN
	SAFE COMBI-C			●	●	●							25-250
	SAFE COMBI-R		●	●	●	●	●	●					20-250

	Application/ Medium			
SAFETY				
SAFE	Your complete safety system			
	Full lift/Standard safety valve with flanges - closed bonnet - closed lifting device - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1	Chemical Industry, processing industry, plant manufacturing	Medium: Steam, aggressive gases, vapours and liquids	
SAFE-P				
	Standard safety valve with flanges - closed bonnet - closed lifting device - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1	Chemical Industry, processing industry, plant manufacturing	Medium: Steam, aggressive gases, vapours and liquids	
SAFE-P 920				
	Standard safety valve with flanges - closed bonnet - closed lifting device - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1	Chemical Industry, processing industry, plant manufacturing	Medium: Steam, aggressive gases, vapours and liquids	
SAFE-TC				
	Full lift/Standard safety valve with thread connection - closed bonnet - closed lifting device - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1	Industrial installations, processing technology, plant manufacturing, etc.	Medium: Steam, aggressive gases, vapours and liquids	
SAFE-TCP				
	Standard safety valve with thread connection - closed bonnet - closed lifting device - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1	Chemical Industry, processing industry, plant manufacturing	Steam, aggressive gases, vapours and liquids	
SAFE-TCS				
	Standard safety valve with thread connection - closed bonnet - closed lifting device - for horizontal application - acc. to VdTÜV sheet 100, AD2000-A2 and EN ISO 4126-1	Chemical Industry, processing industry, plant manufacturing	Steam, aggressive gases, vapours and liquids	
SAFE-SN ANSI				

	Application/ Medium			
	ANSI-Full lift/Standard safety valve with flanges - closed lifting device - ASME	Industrial installations, processing technology, plant manufacturing, etc	Steam, neutral gases, vapours and liquids	
REYCO® R				
				
REYCO® RL				
				
SAFE COMBI-C				
				
SAFE COMBI-R				
				

	You may also Need			
Series SAFE				
SAFE	SAFE 920P	PREDU	STEVI®	
SAFE	SAFETY		CONTROL	
			440,441,445,446	
				
SAFE-P	STRAINER	SAFE • 900	SAFE • TCP 961,962,963	FABA • PLUS
SAFE	ISOLATION	SAFETY	SAFETY	ISOLATION
				
SAFE-P 920	SAFE • 900	SAFE • TCP 961,962,963	STEVI® 470	FABA • PLUS
SAFE	SAFETY	SAFETY	CONTROL	ISOLATION
				
SAFE-TC	SAFE • 900	SAFE • TCP 961,962,963	STEVI® 470	FABA • PLUS
SAFE	SAFETY	SAFETY	CONTROL	ISOLATION
				
SAFE-TCP	SAFE • 900	STEVI®	CONA • S,SC,SC PLUS	FABA • PLUS
SAFE	SAFETY	CONTROL	STEAM TRAP	ISOLATION
		440,441,445,446		
				
SAFE-TCS	SAFE • TCP 961,962,963	STEVI®	CONA • S,SC,SC PLUS	FABA • PLUS
	SAFETY	CONTROL	STEAM TRAP	ISOLATION
		440,441,445,446		
				

P		You may also Need			
	SAFE-SN ANSI	STEVI® ANSI CONTROL 470,470	ZETRIX® 016 ISOLATION	CONA® TD STEAM TRAP	
					
	REYCO® R				
					
	REYCO® RL				
					
	SAFE COMBI-C				
					
	SAFE COMBI-R				
					

[illegible]

[illegible]

Operating Range	Series	Category Known As 1	Category Known As 2	Figure	PN	DN	Material	Material Name	Connection	Form	Temp./*body
SAFETY	SAFE-SN ANSI	SAFETY	FAIL-SAFE	35912	ANSI300	6"x10"	SA216WCB	CARBON STEEL	FLANGE	ANGLE PATTERN	-60°C - 450°C
SAFETY	SAFE-SN ANSI	SAFETY	FAIL-SAFE	35912	ANSI300	6"x8"	SA216WCB	CARBON STEEL	FLANGE	ANGLE PATTERN	-60°C - 450°C