



Operating Range:
Steam Trap



Category
TD TRAPS

Connection
SCREWED

Form
ANGLE PATTERN

TRAPS													
THUMBNAIL	SERIES	FIGURE											DN
	TD TRAPS	AV13 (AV270)											15-25

	Application/ Medium			
Series Traps				
AV13 (AV270)	INVESTMENT CASTING SS THERMODYNAMIC STEAM TRAP, SCREWED FEMALE BSP PARALLEL THREADS (BS-21)			
TD TRAPS				
	Body: 900 Psig Hyd. Seat & Back Seat: 450 Psig Hyd.	Suitable for Steam	Steam Distribution, Heating Systems, Process equipment, Steam Tracing, Heat Exchangers, Steam Heating, Chemical Reactors, Utility Systems	Complete with inbuilt Strainer



You may also Need

Series Traps

AV13 (AV270)

TD TRAPS



ISOLATION

DECA SWING CHECK FIG. 049

DN 15 - DN 80



CONTROL

MD84 BALL VALVE

DN 15 - DN 25



ISOLATION

DECA GATE VALVE FIG. 067

DN 15 - DN 100



TRAP

DECA SIGHT GLASS FIG. 088

DN 10 - DN 50



Operatling Range	Series	Category Known As 1	Category Known As 2	Figure	PN	DN	Material	Material Name	Connection	Form	Temp./*body
TRAPS	TD TRAPS	THERMODYNAMIC STEAM TRAPS	STEAM SEPARATOR	AV13 (AV270)		DN 15	ASTM A217 Gr. CA15	CAST STAINLESS STEEL	SCREWED	ANGLE	UP TO 425°C
TRAPS	TD TRAPS	THERMODYNAMIC STEAM TRAPS	STEAM SEPARATOR	AV13 (AV270)		DN 20	ASTM A217 Gr. CA15	CAST STAINLESS STEEL	SCREWED	ANGLE	UP TO 425°C
TRAPS	TD TRAPS	THERMODYNAMIC STEAM TRAPS	STEAM SEPARATOR	AV13 (AV270)		DN 25	ASTM A217 Gr. CA15	CAST STAINLESS STEEL	SCREWED	ANGLE	UP TO 425°C